



AN-2 Stereo Simulator

The versatile sound processor designed to create a wide range of effects including convincing stereo from any mono source.

How the AN-2 Stereo Simulator Works

The Studio Technologies AN-2 Stereo Simulator utilizes new discoveries in the way the human brain processes sound information.

All natural musical instruments, whether singly or in groups, emit complex sounds with the overtones and room reflections arriving at the two ears in different patterns of phase, intensity,

and time relationships. These relationships create the subjective impression of space and depth.

The AN-2 Stereo Simulator creates two incoherent signals from one source; simulating a stereo perception at the ears of the listener.

Applications

Recording Studios Many times, multi-track recording of voices, an instrument or group of instruments must be assigned to a single track. This results in the loss of the complex overtones and relationships in their true sound.

The AN-2 Stereo Simulator recreates that stereo space and depth. This makes it especially useful with purely electronic instruments such as synthesizers and guitars—instruments usually assigned to a pan pot during mixdown (a mono device). The AN-2 Stereo Simulator creates a much more pleasing “spread” to the sound, allowing the instrument to be heard even in the most complex mixes.

Also, by using the AN-2 Stereo Simulator’s modulation feature, many new effects are possible such as stereo chorusing and stereo pitch bends.

The AN-2 Stereo Simulator has a place in both small and large studios as a track saver and versatile enhancer.

Broadcast & Film Unlike most outboard devices such as time delays, harmonizers and equalizers, the AN-2 Stereo Simulator is *fully mono compatible*. This means recordings produced with the AN-2 Stereo Simulator suffer no balance distortion when heard on AM radio.

The AN-2 Stereo Simulator is also a valuable resource for television broadcasters that offer stereo transmission since much of the material they must broadcast is, in fact, monaural.

And it’s ideal for converting mono film tracks to a fuller, more contemporary “stereo” sound for either broadcast or theatre use.

As a very affordable method for creating stereo sound from mono materials, the AN-2 Stereo Simulator is without equal.

Performance Highlights

- Restores natural timbre of acoustic instruments—adds warmth and reality to synthesized ones.
- Completely mono-compatible—no fade-outs or phase problems.
- Simulates the sound of a spaced pair of microphones without loss of mono compatibility.
- Simulates space without reverberation by using random, non-recursive filter techniques.
- Adds “air” and “definition” to mix, reducing the need for equalization.
- Variable width control allows “spread” and “size” of image to match sound.

**STUDIO
TECHNOLOGIES
INC.**

5520 West Touhy Avenue
Skokie, Illinois 60077 U.S.A.
(847) 676-9177
Fax (847) 982-0747
www.studio-tech.com



AN-2 Specifications

Input and Output Levels: Selectable -10 or +4dBm,
electronically balanced
Frequency Response: 20Hz to 15kHz \pm 2dB
Distortion: 0.2% THD
Dynamic Range: 90dB
Signal to Noise Ratio: 70dB

Power: 115/230V, 50-60Hz, 10 watts
Dimensions: 19.00 inches wide (48.3cm)
1.73 inches high (4.4cm)
7.00 inches deep (17.8cm)
(one standard rack space)
Weight: 5 pounds (2.8kg)

Specifications subject to change without notice.

**STUDIO
TECHNOLOGIES
INC.**

5520 West Touhy Avenue
Skokie, Illinois 60077 U.S.A.
(847) 676-9177
Fax (847) 982-0747
www.studio-tech.com