



## Live-Link™ Remote Camera Interface System Feature-by-Feature Comparison Chart

Live-Link Version	Live-Link Mini		Live-Link Jr.	Live-Link Sr. "04X" Series		Live-Link Sr. "05X" Series	Live-Link Sr. "06X" Series	Live-Link Sr. "07X" Series	Live-Link Sr. "08X" Series
Camera End Unit	LLM-CA-105		LLJR-CA-101/105	LL-3G-CA-041/045		LL-3G-CA-051/055	LL-3G-CA-061/065	LL-3G-CA-075/076	LLSR-CA-085/086
Truck End Unit / Control Room Unit	LLM-TE-107	LLM-TE-109	LLJR-TE-101	LL-3G-CR-041/042/045/046	LL-3G-CR-043/044/047/048	LL-3G-CR-051/052/055/056	LL-3G-CR-061/062/065/066	LL-3G-CR-075/076	LLSR-CR-085/086
<b>Digital Video Paths (3G/HD/SD-SDI)</b>									
Camera End to Truck End / Control Room	1		1	2		3	2	5	4
Truck End / Control Room to Camera End	1	1	1	2		2	2	1	2
<b>Analog Video Paths (NTSC/PAL)</b>									
Control Room to Camera End							1 (Tru-Sync™ technology)		
Mic/Line Inputs (Camera End)			2	4		4	4	4	4
Mic/Line Outputs (Truck End / Control Room)			2	4		4	4	4	4
De-Embed Audio Outputs (Truck End)	4	2	2						
<b>Line/IFB Returns (Camera End)</b>									
Line Outputs	2		2	2		2	2	2	2
IFB Outputs (powered)	1		1	1		1	1	1	1
Party-Line Intercom (Camera End)	Powered, on/off selectable		Powered	Powered		Powered	Powered	Powered	Powered
Party-Line Intercom (Truck End)	Powered, on/off selectable		Powered, on/off selectable		Powered, on/off selectable				
4-Wire Intercom (Truck End / Control Room)	1 channel		1 channel	2 channels		2 channels	2 channels	2 channels	2 channels
<b>Ethernet Transport</b>									
Async Data Transport			1 (RS-422)	1 (RS-422), 1 (RS-232)		1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)
Contact Closures (GPI/GPO)			1	2		2	2	2	2
Optical Fibers (Single Mode)	1		2	2		2	2	2	2
Optical Connectors (Camera End)	1 ST		opticalCON® DUO, 2 ST, or 1 ST	opticalCON DUO or 2 ST		opticalCON DUO or 2 ST	opticalCON DUO or 2 ST	2 ST	2 ST
Optical Connectors (Truck End / Control Room)	1 ST		2 ST or 1 ST	opticalCON DUO or 2 ST		opticalCON DUO or 2 ST	opticalCON DUO or 2 ST	2 ST	2 ST
<b>Enclosure Type</b>									
Camera End	Portable		Portable	Portable		Portable	Portable	Portable or Rack-Ready	Portable or Rack-Ready
Truck End / Control Room	Rack-Mount	Portable	Rack-Mount	Portable or Rack-Ready		Portable or Rack-Ready	Portable or Rack-Ready	Portable or Rack-Ready	Portable or Rack-Ready
<b>Camera End Power</b>									
Battery (Anton/Bauer® standard, V-mount optional)	•		•	•		•	•	Portable only	Portable only
10-18 Vdc (external power supply included)	•		•	•		•	•	•	•
10-50 V (using hybrid/fiber cable)			•	Optional		Optional	Optional		
<b>Truck End / Control Room Power</b>									
Battery (Anton/Bauer standard, V-mount optional)	•			Portable only		Portable only	Portable only	Portable only	Portable only
10-18 Vdc (external power supply included)	•		•	•		•	•	•	•
100-240 V, 50/60 Hz	•		•						