



## Live-Link™ Remote Camera Interface System Feature-by-Feature Comparison Chart

Live-Link Version	Live-Link Jr.	Live-Link Sr. "04X" Series		Live-Link Sr. "05X" Series	Live-Link Sr. "06X" Series	Live-Link Sr. "07X" Series	Live-Link Sr. "08X" Series
Camera End Unit	LLJR-CA-101/105/106	LL-3G-CA-041/045		LL-3G-CA-051/055	LL-3G-CA-061/065	LL-3G-CA-075/076	LLSR-CA-085/086
Truck End Unit / Control Room Unit	LLJR-TE-101/106	LL-3G-CR-041/042/045/046	LL-3G-CR-043/044/047/048	LL-3G-CR-051/052/055/056	LL-3G-CR-061/062/065/066	LL-3G-CR-075/076	LLSR-CR-085/086
Digital Video Paths (3G/HD/SD-SDI)							
Camera End to Truck End / Control Room	1	2		3	2	5	4
Truck End / Control Room to Camera End	1	2		2	2	1	2
Analog Video Paths (NTSC/PAL)							
Control Room to Camera End					1 (Tru-Sync™ technology)		
Mic/Line Inputs (Camera End)	2	4		4	4	4	4
Mic/Line Outputs (Truck End / Control Room)	2	4		4	4	4	4
De-Embed Audio Outputs (Truck End)	2						
Line/IFB Returns (Camera End)							
Line Outputs	2	2		2	2	2	2
IFB Outputs (powered)	1	1		1	1	1	1
Party-Line Intercom (Camera End)	Powered	Powered		Powered	Powered	Powered	Powered
Party-Line Intercom (Truck End)	Powered, on/off selectable		Powered, on/off selectable				
4-Wire Intercom (Truck End / Control Room)	1 channel	2 channels		2 channels	2 channels	2 channels	2 channels
Ethernet Transport		10/100/1000		10/100/1000	10/100/1000	10/100/1000	10/100/1000
Async Data Transport	1 (RS-422)	1 (RS-422), 1 (RS-232)		1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)	1 (RS-422), 1 (RS-232)
Contact Closures (GPI/GPO)	1	2		2	2	2	2
Optical Fibers (Single Mode)	2	2		2	2	2	2
Optical Connectors (Camera End)	opticalCON® DUO, 2 ST, or 1 ST	opticalCON DUO or 2 ST		opticalCON DUO or 2 ST	opticalCON DUO or 2 ST	2 ST	2 ST
Optical Connectors (Truck End / Control Room)	2 ST or 1 ST	opticalCON DUO or 2 ST		opticalCON DUO or 2 ST	opticalCON DUO or 2 ST	2 ST	2 ST
Enclosure Type							
Camera End	Portable	Portable		Portable	Portable	Portable or Rack-Ready	Portable or Rack-Ready
Truck End / Control Room	Rack-Mount	Portable or Rack-Ready		Portable or Rack-Ready	Portable or Rack-Ready	Portable or Rack-Ready	Portable or Rack-Ready
Camera End Power							
Battery (Anton/Bauer® standard, V-mount optional)	•	•		•	•	Portable only	Portable only
10-18 Vdc (external power supply included)	•	•		•	•	•	•
10-50 V (using hybrid/fiber cable)	•	Optional		Optional	Optional		
Truck End / Control Room Power							
Battery (Anton/Bauer standard, V-mount optional)		Portable only		Portable only	Portable only	Portable only	Portable only
10-18 Vdc (external power supply included)	•	•		•	•	•	•
100-240 V, 50/60 Hz	•						